

PICO DISPENSERS

MADE
IN
ITALY

EN. Diesel transfer centrifugal pump unit. Vertical installation with inbuilt connection. Basic equipment includes suction and delivery pipe, manual nozzle, bottom suction filter, integrated switch. Available with both electronic turbine metres (precision +/- 1%) and automatic nozzle. Battery or mains powered. Universal motor with double insulated casing. Power cables: 2 metres with Shuko plug (230 VAC; 3 metres with clips (12 and 24 V DC). 4 metre fuel pipe. 2" BSP and M 64x4 drum connection.

ZH. 离心式柴油加油设备。该设备内置接头，垂直安装。标配带有吸油和送油管、手动加油枪、吸油底阀、内置开关。可选数字式涡轮计量器(精度+/- 1%)和自动加油枪。电池或电网供电。通用电机连双层绝缘外壳。电缆：2米长连Shuko插头(230 VAC)；3米长电缆带电瓶夹(12和24 VDC)。4米长油管。2" BSP或M 64x4油桶接口连接件。

PT. Grupo de bomba centrífuga para transferência de gasóleo. Instalação vertical com engate integrado. Equipamento básico: tubo de aspiração e descarga, pistola manual, filtro no fundo na aspiração, interruptor integrado. Há disponíveis versões com contador de litros electrónico de turbina (precisão +/- 1%) e pistola automática. Alimentação por bateria ou linha eléctrica. Motor universal com cárter de isolamento duplo. Cabos de alimentação de: 2 metros com ficha Shuko (230 VAC); 3 metros com grampos (12 e 24 V. C.C.). Tubo para carburante de 4 metros. Engate no tambor 2" BSP e M 64x4.

PERFORMANCE

- Flow-rate up to 35 l/min
- AC and DC versions available

- 流量达35公升/分钟
- 有交流和直流型可选

- Caudal até 35 l/min
- Disponível na versão AC e DC

PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
Versions with meter					
F00202020	4,8	10,6	360x360x180	14,2x14,2x7,1	1
F00202030	5,8	12,8	360x360x180	14,2x14,2x7,1	1
F00202060	4,8	10,6	360x360x180	14,2x14,2x7,1	1
F00202070	5,8	12,8	360x360x180	14,2x14,2x7,1	1
F00202100	4,8	10,6	360x360x180	14,2x14,2x7,1	1
F00202110	5,8	12,8	360x360x180	14,2x14,2x7,1	1
Versions without meter					
F00202000	4,8	10,6	360x360x180	14,2x14,2x7,1	1
F00202010	5,8	12,8	360x360x180	14,2x14,2x7,1	1
F00202040	4,8	10,6	360x360x180	14,2x14,2x7,1	1
F00202050	5,8	12,8	360x360x180	14,2x14,2x7,1	1
F00202080	4,8	10,6	360x360x180	14,2x14,2x7,1	1
F00202090	5,8	12,8	360x360x180	14,2x14,2x7,1	1



DISPENSERS

Flow-rate

up to
35 l/min
(up to 9 gpm)

PIUSI®

DISPENSERS

PUMPS

METERS

NOZZLE
METERS

NOZZLE

SPECIAL
EQUIPMENTS

FLUID
MONITORING

ACCESSORIES

FILTERING

Base version
without meter



Version with meter

FEATURES

On/Off switch



Electric cable



Electric cables length
6 m with clamps

ON REQUEST

Meter K24



Automatic nozzle



PRODUCTS' RANGE TECHNICAL DATA

PROBOOK RANGE TECHNICAL DATA

Code	Description	Fluids	Flow-rate		Voltage			Pump	Duty cycle	Nozzle	Hose		Foot filter
		type	l/min	gpm	AC V/Hz	DC Volt	Power Watt	Amp. max.	mod.	min.	type	length	
Versions with meter													
F00202020	PICO 230 K24 M	A D W	35	9	230/50	224	1	Pico	-	Man.	4 m.	3/4"	YES
F00202030	PICO 230 K24 A	A D W	30	8	230/50	224	1	Pico	-	Aut.	4 m.	3/4"	YES
F00202060	PICO 12 K24 M	A D W	30	8	12	110	9	Pico	30	Man.	4 m.	3/4"	YES
F00202070	PICO 12 K24 A	A D W	25	7	12	110	9	Pico	30	Aut.	4 m.	3/4"	YES
F00202100	PICO 24 K24 M	A D W	30	8	24	135	5,5	Pico	30	Man.	4 m.	3/4"	YES
F00202110	PICO 24 K24 A	A D W	25	7	24	135	5,5	Pico	30	Aut.	4 m.	3/4"	YES
Versions without meter													
F00202000	PICO 230 M	A D W	35	9	230/50	224	1	Pico	-	Man.	4 m.	3/4"	YES
F00202010	PICO 230 A	A D W	30	8	230/50	224	1	Pico	-	Aut.	4 m.	3/4"	YES
F00202040	PICO 12 M	A D W	30	8	12	110	9	Pico	30	Man.	4 m.	3/4"	YES
F00202050	PICO 12 A	A D W	25	7	12	110	9	Pico	30	Aut.	4 m.	3/4"	YES
F00202080	PICO 24 M	A D W	30	8	24	135	5,5	Pico	30	Man.	4 m.	3/4"	YES
F00202090	PICO 24 A	A D W	25	7	24	135	5,5	Pico	30	Aut.	4 m.	3/4"	YES

Upon request it is available with different voltages and 60 Hz frequency